

US006849285B2

(12) United States Patent

Masek et al.

(10) Patent No.: US 6,849,285 B2

(45) **Date of Patent:** Feb. 1, 2005

(54) SEALED CARTRIDGE FOR MAKING A BEVERAGE

(75) Inventors: Petr Masek, Granges (CH); Alfred

Yoakim, St-Legier-La-Chiesaz (CH)

(73) Assignee: Nestec S.A., Vevey (CH)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 404 days.

(21) Appl. No.: 09/954,957

(22) Filed: Sep. 18, 2001

(65) Prior Publication Data

US 2002/0015768 A1 Feb. 7, 2002

Related U.S. Application Data

(63)	Continuation of application No. PCT/EP00/01752, filed on
	Mar. 2, 2000.

(51) **Int. Cl.**⁷ **A23F 5/26**; B65B 29/02; A47J 31/40

References Cited

(56)

U.S. PATENT DOCUMENTS

2,436,291 A * 2/1948 Daniel 2,778,739 A * 1/1957 Rodth 2,848,130 A * 8/1959 Rodth 2,905,075 A * 9/1959 Liebelt 2,968,560 A * 1/1961 Goros 3,292,527 A * 12/1966 Stasse 3,403,617 A * 10/1968 Campe 3,589,272 A * 6/1971 Bouladon 3,607,297 A * 9/1971 Fasand 3,628,444 A * 12/1971 Mazza

3,719,505	Α	*	3/1973	Mazza	
3,812,273	Α	:	5/1974	Schmidt	
4,136,202	Α		1/1979	Favre	426/77
4,226,333	Α	:	10/1980	Percarpio	
4,236,647	Α	o ķ o	12/1980	Kotturan	
4,301,936	Α	*	11/1981	Percarpio	
4,773,552	Α	o ķ o	9/1988	Boege et al.	
4,846,052	Α	*	7/1989	Favre et al.	
5,008,013	Α	o ķ o	4/1991	Favre et al.	
5,111,946	Α	*	5/1992	Glanz	
5,202,093	Α	o ķ o	4/1993	Cloyd	
5,242,702	A	*	9/1993	Fond	

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

EP	0 512 468	11/1992
EP	0 512 470	11/1992
FR	2 373 999	7/1978
FR	2 668 451	4/1992

Primary Examiner—Steve Weinstein (74) Attorney, Agent, or Firm—Winton & Strawn LLP

(57) ABSTRACT

The invention relates to a sealed cartridge, provided to be extracted under pressure, containing a substance (15) for preparing a beverage, comprising a dish (9) with a bottom (10) and a side wall (11), having substantially the shape of a frustum of a cone, and a circular edge with a diameter greater than the bottom, and a cover (12) welded to the periphery of the edge of the dish, in which the cover (12) consists of a flexible material which is impermeable to oxygen, chosen from the group consisting of aluminum, an aluminum/plastic composite, an aluminum/plastic/paper composite, pure or multi-layer plastic, the said cartridge not comprising a filter or a weakening zone and the cover being intended to be torn only through the effect of the force of the extraction fluid when extraction starts, the said cartridge comprising, in the dish at the level of the bottom, a barrier (13) that is automatically resealable against leakage of the substance upon withdrawal of the fluid injection needle.

17 Claims, 2 Drawing Sheets

